

DECLARATION OF PERFORMANCE

№ 102/07.01.2016

1. **Heating fireplaces**

2. **K2CPW10** /code 3800215092022, 3800215092527, 3800215092657, 3800215092404, 3800215092145, 3800215092947, 3800215092305/;
K22CPW10 /code 3800215092053, 3800215092558, 3800215092435, 3800215092640, 3800215092923/;
S1W10 /code 3800215093135, 3800215093630, 3800215093142, 3800225973090, 3800215093852, 3800215093906, 3800215093913; 3800215093302/;
S2W10 /code 3800215093159, 3800215093166, 3800225973816, 3800215093654, 3800225973168, 3800215093647, 3800215093661, 3800215093869, 3800215093319/;
SKW10 /code 3800215093111, 3800215093623, 3800215093128, 3800225973045/;
SBW10 /code 3800215093104, 3800215093609, 3800215093890/

3. The products are intended for heating of residential and public premises using solid fuel /wooden briquettes or dry wood/

4. Prity 95 ltd, Lyaskovets, 33, M. Raykovich st.

5. System No.3 according to item 1.4 of Enclosure V of Regulations 305/2011 of EU.

6. **Termoplam EOOD Sofia, residential complex "Razsadnika-Konyovitsa", bl.No.82, entrance B, NB 2608** has performed an Initial test of the type according to system 3 according to **BSS EN 13240:2006 "Room heating appliances for solid fuel - requirements and test methods"**.

And has issued a **Report for Accompanying export document No. NB0002/26.10.2015.**

7. Declared performance parameters

Essential Characteristics	Performance parameters	Harmonic technical specification
Fire protection	Corresponds	BSS EN 13240
Emissions from the combustion products	Emissions of CO 0,0919% (966 mg/MJ) Dust content 32 mg/Nm ³ (21,2 mg/MJ) Content of NOx 81 mg/Nm ³ (56,6 mg/MJ) Content of CxHy 65.7 mg/Nm ³ (45,4 mg/MJ)	BSS EN 13240 BimSchV
Temperature of the surfaces	Corresponds	BSS EN 13240
Electrical safety	NRD	
Possibility for cleaning	Corresponds	BSS EN 13240
Maximum operating pressure	Maximum operating pressure 1 bar	BSS EN 13240
Temperature of the flue gases	Temperature of the flue gases 279,6°C	BSS EN 13240
Mechanical safety /maintenance of a chimney/	Corresponds	BSS EN 13240
Heat output / Energy Efficiency	Spatial heat flow 6 kW Heat output of the heat exchanger Nominal 7,1 kW Maximum 10 kW Energy Efficiency 77,6 %	BSS EN 13240

8. The performance parameters of the products, indicated in items 1 and 2 correspond to the declared performance parameters in item 7.

The present Declaration for performance parameters is issued entirely on the responsibility of the producer, indicated in item 4.

Signed for and on behalf of the producer by

Aleksandar Petrov Geranliev – manager

Lyaskovets 07.01.2016

