

# DECLARATION OF PERFORMANCE

№ 108/18.04.2016

## 1. Heating fireplaces

2. **K2** /code 3800215091070, 3800215091575, 3800215091186, 3800225971928, 3800215091285, 3800215091148/,  
**K2 N** /code 3800215091759, 3800215091872, 3800215091926, 3800215091254/,  
**K2CP** /code 3800215092046, 3800215092541, 3800215092534, 3800215092138, 3800215092039, 3800215092596, 3800215092930, 380  
**K12** /code 3800225971331, 3800225971324, 3800215091773/0215092091/,  
**K22** /code 3800215091230, 3800215091742, 3800215091735, 3800225971102, 3800215091919, 3800215091247/,  
**K22-E** /code 3800215091223, 3800215091865, 3800225971126, 3800225971409/,  
**K22CP** /code 3800215092015, 3800215092510, 3800215092602, 3800215092633, 3800215092916/,  
**S1** /code 3800215093005, 3800215093500, 3800215093838, 3800225973403, 3800215093272/,  
**S2** /code 3800215093012, 3800215093517, 3800225973083/,  
**K2-RK** /code 3800215092213, 3800215092244, 3800215092251, 3800215092206/

3. The products are intended for heating of residential and public premises using solid fuel /wooden briquettes or dry wood/

4. Prity 95 Ltd, Lyaskovets, 33, M. Raykovich st.

5. System No.3 according to item 1.4 of Enclosure V of Regulations 305/2011 of EU.

6. **Termoplam EOOD Sofia, residential complex "Razsadnika-Konyovitsa", bl.No.82, entrance Б, NB 2608** has performed an Initial test of the type according to system 3 according to **BSS EN 13240:2006 "Room heating appliances for solid fuel - requirements and test methods"**.

And has issued a **Report for Accompanying export document No. № 10/11.02.2016**.

## 7. Declared performance parameters

Essential Characteristics	Performance parameters	Harmonic technical specification
Fire protection	Corresponds	BSS EN 13240
Emissions from the combustion products	Emissions of CO 0,0633 % (530,1mg/MJ) Dust content 30,24 mg/Nm <sup>3</sup> (20,3 mg/MJ) Content of NOx 95 mg/Nm <sup>3</sup> (66,1 mg/MJ) Content of CxHy 16,56 mg/nm <sup>3</sup> (11,5 mg/MJ)	BSS EN 13240 BimSchV
Temperature of the surfaces	Corresponds	BSS EN 13240
Electrical safety	NRD	
Possibility for cleaning	Corresponds	BSS EN 13240
Maximum operating pressure	NRD	BSS EN 13240
Temperature of the flue gases	Temperature of the flue gases 329,8°C	BSS EN 13240
Mechanical safety /maintenance of a chimney/	Corresponds	BSS EN 13240
Heat output / Energy Efficiency	Spatial heat flow 10 kW Energy Efficiency 77,4 %	BSS EN 13240

8. The performance parameters of the products, indicated in items 1 and 2 correspond to the declared performance parameters in item 7.

The present Declaration for performance parameters is issued entirely on the responsibility of the producer indicated in item 4.

Signed for and on behalf of the producer by

Aleksandar Petrov Geranliev – manager

Lyaskovets 18.04.2016

