

# DECLARATION OF PERFORMANCE

№ 140/28.11.2017

**1. Fireplaces for building-in**

2. **PRITY CW28** /code 3800215095153, 3800215095719, 3800215095702, 3800215095931, 3800215095955/  
**PRITY 2CW28** /code 3800215095269, 3800215095627, 3800215095771, 3800215095566, 3800215095573/  
**PRITY 3CW28** /code 3800215095290, 3800215095641/  
**PRITY GW28** /code 3800215095207, 3800215095740, 3800215095597/  
**PRITY PW28TV** /code 3800225975308/  
**PRITY CW35** /code 3800215095160, 3800215095306, 3800225975285, 3800225975087/  
**PRITY 3CW35** /code 3800215095306/

3. The products are intended for heating of residential and public premises using solid fuel /wooden briquettes or dry wood/

4. Prity 95 ltd, Lyaskovets, 33, M.Raykovich st.

5. System No.3 according to item 1.4 of Enclosure V of Regulations 305/2011 of EU.

6. **Termoplam EOOD Sofia, residential complex "Razsadnika-Konyovitsa", bl.No.82, entrance B, NB 2608** has performed an Initial test of the type according to system 3 according to **BSS EN 13229:2006 "Built-in appliances, including fireplaces for solid fuel - requirements and test methods"**.

And has issued a *Report for Accompanying export document No 72/03.11.2017.*

**7. Declared performance parameters**

Essential Characteristics	Performance parameters		Harmonic technical specification	
Fire protection	Corresponds		BSS EN 13229	
Emissions from the combustion products	Emissions of CO	0,0966 % (808,7 mg/MJ)	БДС EN 13229 § 15a B-VG	
	Dust content	30,33 mg/Nm <sup>3</sup> (20,32 mg/MJ)		
	Content of NOx	96,3 mg/Nm <sup>3</sup> (62,87 mg/MJ)		
	Content of CxHy	20,84 mg/Nm <sup>3</sup> (14,51 mg/MJ)		
Temperature of the surfaces	Corresponds		BSS EN 13229	
Electrical safety	NRD			
Possibility for cleaning	Corresponds		BSS EN 13229	
Maximum operating pressure	NRD			
Temperature of the flue gases	Temperature of the flue gases	258,2 °C	BSS EN 13229	
Mechanical safety /maintenance of a chimney/	Corresponds		BSS EN 13229	
Heat output / Energy Efficiency		<u>CW28</u> <u>2CW28</u> <u>3CW28</u> <u>GW28</u> <u>PW28TV</u>	<u>CW35</u> <u>3CW35</u>	
	Spatial heat flow	5 kW	5 kW	BSS EN 13229
	Nominal heat output of the exchanger	28 kW	35 kW	
	Energy Efficiency	78,56 %		

8. The performance parameters of the products, indicated in items 1 and 2 correspond to the declared performance parameters in item 7.

The present Declaration for performance parameters is issued entirely on the responsibility of the producer, indicated in item 4.

Signed for and on behalf of the producer by  
Aleksandar Petrov Geranliev – manager

**Lyaskovets 28.11.2017**

